

Model M122K - 12"



Mounting Feet

- Lowest profile high performance reversibles on the market
- Sealed motor tested in accordance with DIN EN 60529, dust and water proof to IP68
- Quiet, reversible S-blade design
- All glass-filled nylon construction
- Includes (4) 90° mounting feet
- Includes locking mating pigtail connector and rubber spacers for proper spacing off of heat exchanger
- Recommended wire harnesses* (sold separately)
 - Part No. MFA100 (adjustable thermostat)
 - Part No. MFA102 (185° temperature switch)
 - Part No. MFA103 (195° temperature switch)
- Optional brackets* (sold separately)
 - Part No. MFA104 (metal bracket strips)
 - Part No. MFA105 (aluminum brackets)



Fan Harness



Pigtail

TYPICAL PERFORMANCE DATA		
M122K 12" LP REVERSIBLE CHAMPION 12V 225W		
Static In H ₂ O	Total Flow CFM	13.5 VDC AMPS
0.00	1565	13.5
0.10	1456	13.8
0.20	1377	14.3
0.30	1273	14.3
0.40	1183	14.4
0.50	1005	14.4
0.60	862	14.4
0.70	608	14.3
0.80	380	13.5
0.90	251	13.8
1.10	STALL @ 1.1"	15.6

