

Model M166K - 16"



Mounting Feet

- Lowest profile high performance reversibles on the market
- Sealed motor tested in accordance with DIN EN 60529, dust and water proof to IP68
- Quiet, reversible S-blade design
- All glass-filled nylon construction
- Includes (4) 90° mounting feet
- Includes locking mating pigtail connector and rubber spacers for proper spacing off of heat exchanger
- Recommended wire harnesses* (sold separately)
 - Part No. MFA100 (adjustable thermostat)
 - Part No. MFA102 (185° temperature switch)
 - Part No. MFA103 (195° temperature switch)
- Optional brackets* (sold separately)
 - Part No. MFA104 (metal bracket strips)
 - Part No. MFA105 (aluminum brackets)



Fan Harness

Pigtail

| TYPICAL PERFORMANCE DATA | | |
|---|----------------|---------------|
| M166K 16" LP REVERSIBLE CHAMPION 12V 160W | | |
| Static In H ₂ O | Total Flow CFM | 13.5 VDC AMPS |
| 0.00 | 1810 | 12.3 |
| 0.10 | 1680 | 12.8 |
| 0.20 | 1456 | 13.1 |
| 0.30 | 1181 | 13.0 |
| 0.40 | 877 | 12.6 |
| 0.50 | 556 | 12.0 |
| 0.60 | 217 | 11.8 |
| 0.70 | STALL @ 0.7" | 12.1 |

